

ACRYLIC URETHANE SELF-SEAL
SERIES M900
CLEAR**DESCRIPTION:**

M900 Acrylic polyurethane is a clear, two-component self-seal product from the Verinlegno series with outstanding non-yellowing characteristics. The M900 series provides protection against UV light exposure and has excellent chemical resistance. It provides great surface hardness, moisture resistance as well as mar resistance. M900 was specifically designed for kitchen cabinets, bathroom vanities and wooden furniture.

PRODUCT DATA:

PRODUCT CODE:	M900
VISCOSITY:	15 sec (FC#4) (application)
SOLID % by WT:	25% ± 2%
SOLID % by WT:	21 ± 2% (with catalyze)
VOC:	618 g/L
DENSITY:	0.92 gr/L
SHEEN:	3°, 5°, 10°, 20°, 30°, 50°, 70°
SHELF LIFE:	12 months

MIXING RATIO:

M900 ACRYLIC:	5 parts
B42 HARDENER:	1 part
REDUCER:	400-050 (30-40 %)
POT LIFE:	8 hours

DRYING TIMES:

THICKNESS APPLIED:	4-5 wet mils
DUST FREE:	15 minutes
READY TO HANDLE:	60 minutes
READY TO PACK:	12 hours

Note: Drying times may vary depending on thickness applied, temperature and/or humidity.

Warning: Its is not recommended to use a product whose pot life has expired.

APPLICATION:

Substrate should be clean, oil and grease free and well sanded. Ensure product is stirred thoroughly and mixed according to specifications before applying.

APPLICATION EQUIPMENT:

AIR ASSIST	
CONVENTIONNAL	
FINISH THICKNESS:	4-5 wet mils
NUMBER OF COATS:	1 or 2

TYPICAL SYSTEM:

TP WIPING STAIN:	1 hour dry time
M900 Self sealed:	1 coat 4-5 wet mils
M900 Self sealed:	1 coat 4-5 wet mils

STORAGE:

Store in a dry and cool area. Close the container properly after use.



The customer is responsible for following the recommended application procedures. Failure to adhere to these specifications may result in poor appearance or failure of film. This product is for professional use only. Consult your local representative before applying with other manufacturer products. The customer should test the complete system for adhesion, compatibility and performance prior to full scale application. Please refer to the Safety Data Sheet (SDS) for safety information and precautions prior to using this product. We ONLY guarantee our product to conform to our quality. Our responsibility as manufacturer is limited to the cost of the product. Please feel free to contact us at (819) 367-2201 for any further inquiries regarding this product. All information on this product data sheet is subject to change without notice.